


## Piezoelectric Accelerometer

### FEATURES

- ▶ Industrial vibration monitoring
- ▶ High sensitivity
- ▶ Differential output
- ▶ Hermetically welded
- ▶ Internal case insulation
- ▶ Integral cable
- ▶ Certified for use in potentially explosive atmospheres
- ▶ Frequency response:  
0.5 Hz to 5000 Hz
- ▶ Sensitivity:  
100 pC/g
- ▶ Temperature range (operational):  
-55 °C to +260 °C



### DESCRIPTION

The CA 202 accelerometer features a symmetrical shear mode polycrystalline measuring element which has internal case insulation. The transducer is designed for heavy-duty industrial vibration

monitoring and measurement. The accelerometer is fitted with an integral cable protected by a flexible stainless steel tube welded to the case.



Information contained in this document may be subject to Export Control Regulations of the European Union, USA or other countries. Each recipient of this document is responsible for ensuring that transfer or use of any information contained in this document complies with all relevant Export Control Regulations. ECN N/A.

## SPECIFICATIONS

---

### GENERAL

Input power requirements	: None
Signal transmission	: 2-pole system insulated from casing, charge output
Signal processor	: Charge amplifier

### OPERATING

(at +23°C ± 5°C)

Sensitivity (at 120 Hz)	: 100 ± 5 pC/g
Dynamic measuring range (random)	: 0.01 g to 400 g peak
Overload capacity (spikes)	: Up to 500 g peak
Linearity	: ± 1% between 0.01 g and 20 g peak, ± 2% up to 400 g peak
Transverse sensitivity	: ≤ 3%
Resonant frequency (mounted)	: 20 kHz nominal
Frequency response	: ± 5% between 0.5 Hz and 5000 Hz (lower cut off frequency is determined by conditioner used)
Internal insulation resistance	: Min. 10 <sup>9</sup> Ω
Capacitance (nominal)	
• Pole to pole	: 4500 pF for transducer + 105 pF/m of cable
• Pole to casing	: 10 pF for transducer + 210 pF/m of cable

### ENVIRONMENTAL

Temperature range

• Transducer	: -55°C to +260°C operation : -70°C to +280°C survival
• Cable	: -55°C to +200°C operation : -62°C to +250°C survival

Temperature error

• -55°C to +23°C	: 0.25%/°C
• +23°C to +200°C	: 0.08%/°C
• +200°C to +260°C	: 0.25%/°C

Shock acceleration : ≤ 1000 g peak (half sine wave, 1 ms duration)

Explosive atmospheres

	: Available in Ex version
• EC type examination certificate	: LCIE 02 ATEX 6179 X II 1 G (Zones 0, 1, 2) Ex ia IIC T6 to T1
• Voluntary type examination certificate	: LCIE 09 ATEX 1044 X II 3G (Zone 2) Ex nA II T6 to T2



For specific parameters of the mode of protection concerned and special conditions for safe use, please refer to the appropriate "EC type examination certificate". These certificates are available from Vibro-Meter SA on demand.

Corrosion, humidity	: Stainless austenitic steel, hermetically welded
Base strain sensitivity	: 0.1 x 10 <sup>-3</sup> g/με at 250 με peak-peak

## SPECIFICATIONS (Continued)

### MECHANICAL


#### Weight

- Accelerometer (nominal) : 250 g
  - Cable : 135 g/m
  - Cable : 2 pole twisted and shielded
  - Mounting : 4 Allen screws, size M6x35, with M6 spring-lock washers, screw torque 15 Nm.
- No need for electrical insulation of mounting surface.

### CALIBRATION

Dynamic calibration at factory at 5 g peak and 120 Hz (+23°C). No subsequent calibration necessary.

### MECHANICAL DRAWING



## ORDERING INFORMATION

To order please specify:

Type	Designation	Ordering Number
CA202	Standard version, 3 m cable length	144-202-000-205
	Standard version, 6 m cable length	144-202-000-215
	Standard version, 11 m cable length	144-202-000-225
	Standard version, 20 m cable length	144-202-000-235
	Ex version, 3 m cable length	144-202-000-105
	Ex version, 6 m cable length	144-202-000-115
	Ex version, 11 m cable length	144-202-000-125
	Ex version, 20 m cable length	144-202-000-135

## MOUNTING ACCESSORIES

MA 133 Thermal insulation kit : See drawing 809-133-000V011



All statements, technical information, drawings, performance rates and descriptions in this document, whilst stated in good faith, are issued for the sole purpose of giving an approximate indication of the products described in them, and are not binding on Vibro-Meter SA unless expressly agreed in writing. Before acquiring this product, you must evaluate it and determine if it is suitable for your intended application. Unless otherwise expressly agreed in writing with Vibro-Meter, you assume all risks and liability associated with its use. Any recommendations and advice given without charge, whilst given in good faith, are not binding on Vibro-Meter.

Vibro-Meter takes no responsibility for any statements related to the product which are not contained in a current Vibro-Meter publication, nor for any statements contained in extracts, summaries, translations or any other documents not authored by Vibro-Meter. We reserve the right to alter any part of this publication without prior notice.

In this publication, a dot (.) is used as the decimal separator and thousands are separated by spaces. Example : 12345.67890.

### Sales offices

Vibro-Meter has offices in more than 30 countries. For a complete list, please visit our website.

### Your local agent

### Head office

Vibro-Meter SA  
Rte de Moncor 4  
P.O. Box  
CH-1701 Fribourg  
Switzerland

Tel: +41 26 407 11 11  
Fax: +41 26 407 13 01



[www.vibro-meter.com](http://www.vibro-meter.com)

**MEGGITT**  
smart engineering for  
extreme environments